

Tel: 1-800-722-8197 1-631-595-2217 Fax: 1-631-667-5484 EMAIL: sales@challelec.com WEB: www.challengeelectronics.com ISO 9001/14001:2015 Certified

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CAB83LA-01S-1

Rev. 0-2019 RoHS3 & REACH Battery Assembly



Physical Characteristics

MATERIALS


Housing PBT UL94V-0 + 20% GF Black

Contact Spring Steel, T=0.3, Nickel Plated

TEMPERATURE RANGES

Operating -25 to +85 °C
Storage -40 to +105 °C

Cell Type 18650, or equivalent



Revision	Description	Ву	Date
0-2019	Initial Specification Sheet	JL	2019-12-06

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

©2020 Challenge Electronics, Inc. Pub. 20200417120925