



# PRODUCT INFORMATION

Part #: **CE-BCX630AWF**

Revision: 0-2014



DESCRIPTION		FEATURES				
<b>Challenge Electronics Dual Function BEEP or CONTINUOUS Tone; EXTRA Loud</b> Piezoelectric Alarm; <b>6 to 30 Vdc</b> ; <b>A</b> style Rear Panel Mount case; Sound Pressure Level of <b>103 dB(A)</b> at 30 Vdc at 61 cm; <b>2,900 Hz.</b> Output Frequency; <b>Wire Leads 5"</b> Long termination; <b>Fast Beep</b> , 3 pulses per second Rate; <b>RoHS Compliant</b>		<ul style="list-style-type: none"> <li>◆ <b>Reliable Solid State Piezoelectric Technology</b></li> <li>◆ <b>Corrosion resistant Stainless Steel Diaphragm</b></li> <li>◆ <b>Flame Retardant Plastic</b></li> <li>◆ <b>Extended storage temperature</b></li> <li>◆ <b>Hermetically Sealed Alarm</b></li> <li>◆ <b>Water Proof, NEMA 3R, 4X, or 12 with Gasket (not supplied)</b></li> <li>◆ <b>RoHS, Lead Free Compliance</b></li> <li>◆ <b>ISO 9001:2008 &amp; ISO-TS 16949:2009 Certified</b></li> </ul>				
SPECIFICATIONS						
Operating Mode	Extra Loud, Fast Intermittent or Continuous Tones		Pulse Rate	3 ± 10% Pulses per Second		
Operating Voltage	6 to 30 Vdc	Nominal Operating Voltage	24 Vdc	Operating Frequency	2,900 ± 500 Hz.	
Typical Loudness	At 6 Vdc	88±5 dB(A)	At 24 Vdc	101±3 dB(A)	At 30 Vdc	103±3 dB(A)
	SPL is measured at 24" (61 cm), 25°C, Sound Level meter # 2240, Type 2, Fast Response, A-Weighted					
Typical Operating Current	10 mA at 6 Vdc		35 mA at 24 Vdc		40 mA at 30 Vdc	
Operating Temperature	-30°C to +65°C	Storage Temperature	-40°C to +100°C			
Surge Voltage	20% over maximum Operating Voltage for less than 5 minutes					
Polarity Protection	Protected against Reversed Voltage to the Maximum Operating Voltage					
Materials	Alarm Case	Plastic, "A" Case, NORYL™, PX9406 or equal, flame retardant UL 94-V0, Black				
	Diaphragm	Stainless Steel 304				
	Encapsulation	Silicon Potting covering SMD components topped with 2 parts epoxy potting, Black				
	Termination	Three (3) Wires Leads, 18 AWG (7X32), GXL Automotive, Copper, XPLE insulated, 5.0" (127) Long. Struck 0.235 (6.0mm), Red = Common Positive Black = Intermittent Negative, and Blue = Continuous Negative				
Physical Dimensions	Diameter	1.4" (35.6 mm) Ø	Width	Height	1.4" (35.7 mm)	
Panel Mounting	From the Rear with Plastic Ring Nut	Mounting Hole	1.125" (28.6mm) Ø	Max. Panel Thickness	0.25" (6.3mm)	
Approximate Weight	37 grams	Rotor Volume Control	No	Compliance	RoHS	
Available Options	Rotor Volume Control, Water Proof Gasket, Mounting Bracket, and variety of connectors terminated on the Wire Lead ends					
RELIABILITY						
Thermal Operating Temperature Test	96 hours continuous operation at Rated Voltage, at Maximum Rated Operating Temperature *					
	96 hours continuous operation at Rated Voltage, at Minimum Rated Operating Temperature *					
Thermal Storage Temperature Test	96 hours storage at Maximum Rated Storage Temperatures *					
	96 hours storage at Minimum Rated Storage Temperatures *					
Thermal Shock Test	5 cycles of Minimum and Maximum Operating Temperature Each cycle shall be set per diagram below and is 3 hours long *					
Humidity Test	120 Hours at +60°C±2°C. 90-95% RH *					
Salt Spray	Withstand exposure to salt spray per ASTM B117 for a period of 300 hours *					
Water & Dust Exposure	Withstands water submergence and dust exposure per IP-68 *					
Vibration Test	2 Hours at 1.5 mm with 10 to 55 Hz. of vibration frequency to each of 3 perpendicular direction *					
Drop Test	Dropped naturally from 1 meter height onto the surface of 10mm wooden board, 2 directions upper and side of the part are applied *					
Termination Strength	Maximum of 15 pounds (6.8 Kg) load pull test					
* Reliability Test Performance	Parts should conform to original performance within ±3 dB, after 3 hours of recovery and dry period					
Life Test	Intermittent	1,000 hours of a 1 minute on 4 minutes off cycle at room temperature and maximum rated Voltage				
	Continuous	250 hours continuous operation at room temperature and maximum rated Voltage				
Warranty	For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair					



Current Draw and Loudness Vs. Input Voltage		DIMENSIONS		Units	Inches (mm)	Tolerance	0.030 (0.7)										
Typical Output Sound Level ± 4 dB(A), with Type 2 Meter 	Input Current (mA)	FRONT VIEW 		RING NUT 		SIDE VIEW 		REAR VIEW 									
		1.125-24 UNF THREADS MAJOR D 1.118 MINOR D 1.074 PITCH D 1.094		(+) Common (-) Continuous Tone (-) Main Tone													
<b>ALARM MAKING</b> On side Case: Part Number Sound Type Operating Voltage Range / Date Code Challenge Electronics Made in China On Back: Polarity				<b>TYPICAL MOUNTING</b> <table border="1"> <tr> <td>Alarm Threads:</td> <td>1.125-24 UNF Threads, 2A Class, Major 1.118" Ø, Minor 1.063" Ø, Pitch 1.094" Ø</td> </tr> <tr> <td>Ring Nut Threads:</td> <td>1.125-24 UNF Threads, 2B Class, Major 1.120" Ø, Minor 1.073" Ø, Pitch 1.094" Ø</td> </tr> <tr> <td>Mounting Hole:</td> <td>1.25" (31.75 mm) Ø</td> </tr> <tr> <td>Panel Thickness:</td> <td>0.03 (0.75 mm) to 0.25" (6.4 mm)</td> </tr> <tr> <td>Gasket (Optional):</td> <td>1.25" (31.75 mm) ID, 1.40" (35.6 mm) OD, 0.10" (2.54 mm) Thick Rubber,</td> </tr> </table>				Alarm Threads:	1.125-24 UNF Threads, 2A Class, Major 1.118" Ø, Minor 1.063" Ø, Pitch 1.094" Ø	Ring Nut Threads:	1.125-24 UNF Threads, 2B Class, Major 1.120" Ø, Minor 1.073" Ø, Pitch 1.094" Ø	Mounting Hole:	1.25" (31.75 mm) Ø	Panel Thickness:	0.03 (0.75 mm) to 0.25" (6.4 mm)	Gasket (Optional):	1.25" (31.75 mm) ID, 1.40" (35.6 mm) OD, 0.10" (2.54 mm) Thick Rubber,
Alarm Threads:	1.125-24 UNF Threads, 2A Class, Major 1.118" Ø, Minor 1.063" Ø, Pitch 1.094" Ø																
Ring Nut Threads:	1.125-24 UNF Threads, 2B Class, Major 1.120" Ø, Minor 1.073" Ø, Pitch 1.094" Ø																
Mounting Hole:	1.25" (31.75 mm) Ø																
Panel Thickness:	0.03 (0.75 mm) to 0.25" (6.4 mm)																
Gasket (Optional):	1.25" (31.75 mm) ID, 1.40" (35.6 mm) OD, 0.10" (2.54 mm) Thick Rubber,																
<b>PACKAGING</b> 				<b>MARKING</b> <b>Bundle</b> Part Number Other PN if required Quantity Lot and/or Date Code <b>Shipping Box</b> Part Number Other PN (if required) Quantity Lot and/or Date Code PO Number Net Weight Gross Weight Box Number of Boxes <b>Made in China</b>		<b>TRAY</b> Dimensions X1 34.7 cm Y1 34.7 cm Z1 21.2 cm Quantity 42 <b>BUNDLE</b> Dimensions X2 cm Y2 cm Z2 cm <b>SHIPPING BOX</b> Dimensions X3 35 cm Y3 35 cm Z3 22.5 cm Number of Bundles 1 Quantity 250 Approximate Weight 9 Kg.											
Revision	Description			By	Date												