

## CI12E-15T310-C-1

Former P/N: CEEB120B075-915C31P76R

Rev. 2-2019  
RoHS3 & REACH  
Electromagnetic Indicators

PHOTO  
UNAVAILABLE


### Operating Characteristics

#### ELECTRICAL

Rated Voltage	12 VDC
Operating Voltage	9 to 15 VDC
Max Current at Vmax	30 mA

#### ACOUSTIC

Tone Category	Continuous
Description	Steady
Center $f$	3100 $\pm$ 300 Hz
Min SPL at Vrated	85 dB
Test Conditions	10 cm



### Physical Characteristics


#### MATERIALS

Housing	PBT
Diaphragm	Iron
PC Pin	Red Copper

#### TEMPERATURE RANGES

Operating	-20 to +80 °C
Storage	-30 to +85 °C

Weight 2 g



Revision	Description	By	Date
1-2018	Removed polarity protection from specification sheet.	JL	2018-06-20
2-2019	Migrate to new format		2019-06-21

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.