

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CT16E-08T204-1

Former P/N: CEET160B140-50-408-20P7.6LR

Rev. 1-2019
RoHS3 & REACH
Electromagnetic Sound Transducers




Operating Characteristics

ELECTRICAL

Rated Voltage	6 Vo-p
Operating Voltage	4 to 8 Vo-p
Coil Resistance	50 ± 6 Ω
Max Current at V Rated	40 mA

ACOUSTIC

Min SPL at V Rated	85 dB
Test Conditions	10 cm
f _o	2048 Hz



Physical Characteristics

MATERIAL

Housing	Noryl
Diaphragm	Ni-alloy
PC Pin	Tin Plated Copper

TEMPERATURE RANGES


Operating	-40 to +70 °C
Storage	-40 to +85 °C

Weight 5 g

Unless otherwise specified, tolerance: ± 0.5(unit:mm)

Laser Print: CEET160B140
-50-408-20P7.6
LR ⊕ YM

(Date Code: YM:Year, Month ie:12H)



Revision	Description	By	Date
0-2011	Initial Specification Sheet		2011-12-15
1-2019	Migrate to new format. Corrected voltage from Vpp to Vo-p. Updated mechanical drawing with washing label.	JL	2019-09-09

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.