


INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

## CT18E-10T204-2

Former P/N: CET1410W10-60-310-20P65LHR

Rev. 2-2019  
 RoHS3 & REACH  
 Electromagnetic Sound Transducers




### Operating Characteristics

#### ELECTRICAL

Rated Voltage	6.0 Vo-p
Operating Voltage	3.0 to 10.0 Vo-p
Coil Resistance	60 ± 9 Ω
Max Current at V Rated	40 mA

#### ACOUSTIC

Min SPL at V Rated	85 dB
Test Conditions	10 cm
f <sub>o</sub>	2048 ± 200 Hz



### Physical Characteristics


#### MATERIAL

Housing	Plastic, Noryl, Black
Diaphragm	Ni-alloy
PC Pin	Tin Plated Copper

#### TEMPERATURE RANGES

Operating	-30 to +80 °C
Storage	-40 to +85 °C

Weight 7 g



Revision	Description	By	Date
1-2013	Revised Mechanical Dimensions (14x10x10 to 18x14x10)	WS	2013-07-03
2-2019	Migrate to new format	JL	2019-06-21

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.