

CT05E-04S400-10

Former P/N: CEET050M025-17-204-40MR

Rev. 2-2019
 RoHS3 & REACH
 Electromagnetic Sound Transducers




Operating Characteristics

ELECTRICAL

Rated Voltage	3 Vo-p
Operating Voltage	2 to 4 Vo-p
Coil Resistance	17 ± 2 Ω
Max Current at V Rated	80 mA

ACOUSTIC

Min SPL at V Rated	75 dB
Test Conditions	10 cm
f_o	4000 Hz ± 10 %



Physical Characteristics


MATERIAL

Housing	Plastic
Diaphragm	Ni Alloy Disc N50
Solder Pad	Sn Plated Brass

TEMPERATURE RANGES

Operating	-30 to +85 °C
Storage	-40 to +90 °C

Weight 0.5 g



Revision	Description	By	Date
1-2014	Corrected SPL (from 82 to 75)	WS	2014-01-14
2-2019	Migrate to new format	JL	2019-06-21

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.