

Tel: 1-800-722-8197 1-631-595-2217 Fax: 1-631-667-5484 EMAIL: sales@challelec.com WEB: www.challengeelectronics.com ISO 9001/14001:2015 Certified

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CT09E-06T273-2

Former P/N: CEET090A055-40-27P4LR

Rev. 4-2023 RoHS3 & REACH Electromagnetic Sound Transducers




Operating Characteristics

ELEC	TRICAL		
	Rated Voltage	5 Vo-p	
	Operating Voltage	4 to 6 Vo-p	
	Coil Resistance	$40 \pm 4 \Omega$	
	Max Current	60 mA	

ACOUSTIC

Min SPL at V Rated	85 dB
Test Conditions	10 cm
fo	2731 Hz



Physical Characteristics


MATERIAL

Housing	PBT	
Diaphragm	Iron	
PC Pin	Copper	

TEMPERATURE RANGES

Operating	-30 to +85 °C
Storage	-40 to +85 °C

Weiaht	1.0 a





<u>្ត5.5±0.2</u> ្ព	* 99±0.5
4.5	EDOXI.

Revision	Description	Ву	Date
3-2019	Migrate to new format	JL	2019-06-21
4-2023	Added part image.	SK	2023-05-12

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.