


INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CT10E-04T273-1

Former P/N: CEET108C040-15-204-27P4R

 Rev. 1-2019
 RoHS3 & REACH
 Electromagnetic Sound Transducers



Operating Characteristics

ELECTRICAL

Rated Voltage	3.0 Vo-p
Operating Voltage	2.0 to 4.0 Vo-p
Coil Resistance	15 ± 3 Ω
Max Current at V Rated	80 mA

ACOUSTIC

Min SPL at V Rated	90 dB
Test Conditions	10 cm
f _o	2731 ± 500 Hz



Physical Characteristics


MATERIAL

Housing	PPO Plastic Resin (black)
Diaphragm	Iron-Nickel Alloy
PC Pin	Gold Plated Brass

TEMPERATURE RANGES

Operating	-20 to +70 °C
Storage	-30 to +80 °C

Weight 1.0 g



Revision	Description	By	Date
0-2016	Initial Spec	EZ	2016-04-04
1-2019	Migrate to new format	JL	2019-06-21

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.