


INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

## CT16E-12T204-1

Former P/N: CET160B145-45-312-20P76LHR

Rev. 2-2019  
 RoHS3 & REACH  
 Electromagnetic Sound Transducers




### Operating Characteristics

#### ELECTRICAL

Rated Voltage	6.0 Vo-p
Operating Voltage	3.0 to 12.0 Vo-p
Coil Resistance	45 ± 7 Ω
Max Current at V Rated	200 mA

#### ACOUSTIC

Min SPL at V Rated	85 dB
Test Conditions	10 cm
f <sub>o</sub>	2048 ± 300 Hz



### Physical Characteristics


#### MATERIAL

Housing	Plastic, Noryl, Black
Diaphragm	Ni-alloy
PC Pin	Tin Plated Copper

#### TEMPERATURE RANGES

Operating	-40 to +85 °C
Storage	-40 to +85 °C

Weight	6 g
--------	-----



Revision	Description	By	Date
2-2019	Migrate to new format	JL	2019-06-21

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.