

Tel: 1-800-722-8197 1-631-595-2217 Fax: 1-631-667-5484 EMAIL: sales@challelec.com WEB: www.challengeelectronics.com ISO 9001/14001:2015 Certified

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CS16-00P85-03-3

Former P/N: CES160V030BA06PMN850TR

Rev. 4-2020 RoHS3 & REACH Mobile Speakers



Operating Characteristics 120 **ELECTRICAL** Rated Power 0.67 W Short Term Max Power 1.0 W 6 Ω ± 15 % Impedance 100 2000 Hz: 0.6667 W ACOUSTIC: 1 cc Sealed Enclosure 850 Hz ± 20 % fo Freq. Range 850 to 10000 Hz $90 \pm 3 dB$ Rated SPI 2000 Hz: 0.67 W; 10 cm; Distortion <20 % 1000 Hz; .67 W 100 1000 10000

Physical Characteristics MATERIALS 9.0±0.1 3.0 ± 0.15 Plastic Housing Cone Mylar 3x NdFeB Magnet Solder Tin Plated SUS Pad TEMPERATURE RANGES -20 to +70 °C ف Operating 3 Storage -40 to +85 °C Weight 1.5 g 3.6

Revision	Description	Ву	Date
3-2019	Migrate to new format	WS	2019-06-21
4-2020	Added magnet quantity to materials section.	JL	2020-04-02

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.