

## CS34-01P50-03-1

Former P/N: CS34P-0150-031

Rev. 1-2019  
RoHS3 & REACH  
Mobile Speakers



### Operating Characteristics

#### ELECTRICAL

Rated Power	1 W
Short Term Max Power	1.2 W
Impedance	8 $\Omega$ $\pm$ 20 % 2000 Hz; 1 W

#### ACOUSTIC: 3CC Sealed Enclosure

$f_o$	500 Hz $\pm$ 20 % 1 W
Freq. Range	500 to 20000 Hz
Rated SPL	90 $\pm$ 3 dB 2000 Hz; 1 W; 10 cm;
Distortion	<5 % at 1000 Hz; 1 W



### Physical Characteristics


#### MATERIALS

Housing	PBT
Cone	PEEK
Magnet	NdFeB
Solder Pad	Stainless Steel

#### TEMPERATURE RANGES

Operating	-20 to +70 °C
Storage	-40 to +85 °C

Weight 5 g


Tolerance:  $\pm$  0.2

Revision	Description	By	Date
0-2018	Initial Specification Sheet	JL	2018-09-12
1-2019	Migrate to new format.	CF	2019-06-24

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

©2019 Challenge Electronics, Inc. 20190826155535